

WOLLENSAK 4100 CORDLESS




WOLLENSAK 4100 SPECIFICATIONS:

FREQUENCY RESPONSE:
 120-6000 cps $\pm$ 3 db
 WOW AND FLUTTER RMS: 0.35%
 SIGNAL TO NOISE RATIO:
 Better than -45 db
 POWER OUTPUT: 250 mW
 TRACK WIDTH: 0.06"
 PLAYING TIME PER CARTRIDGE:
 One hour
 TAPE SPEED: 1 7/8 ips.
 SIZE: 4 1/2" Width; 7 3/4" Height;
 2 1/4" Depth
 WEIGHT: 3 Pounds


BATTERY-OPERATED CARTRIDGE TAPE RECORDER OFFERS COMPLETE PORTABILITY. Record a business meeting, classroom lecture or an interview. Easy to load with compact tape cartridges. Easy to use—one 4-position function switch controls all operating modes.

FEATURES OF THE WOLLENSAK 4100: ☐ Records one hour. ☐ Solid-state for instant warmup and reliability. ☐ Constant speed capstan drive. ☐ VU meter for correct recording level and battery condition. ☐ Separate record level and volume controls. ☐ Dynamic microphone with remote start/stop switch. ☐ Record lock safety. ☐ Sturdy construction. ☐ Fully transistorized amplifier. ☐ High efficiency speaker. ☐ Patch cord for external recording/playback. ☐ Complete with sensitive dynamic microphone, carrying case, three SCOTCH® Brand Magnetic Tape Cartridges and standard "C" batteries.

NEW WOLLENSAK 4100 OFFERS THESE UNIQUE FEATURES:




Separate record level and playback volume controls for operating convenience.



Patch cord to record and playback through any sound system.



One 4-position switch controls all operating modes: fast off, forward, rewind, play/record or off.



Solid-state amplifier for rugged reliability, assures good volume and frequency response.



Capstan drive for constant tape speed. 2 track operation offers one full hour of recording.



VU meter indicates correct recording level and condition of batteries.

Revere-Mincom Division **3M** COMPANY
 2501 HUDSON ROAD • ST. PAUL, MINNESOTA 55119



WOLLENSAK 1500 SS

Famous for operating convenience, precision performance, and long-term reliability, the 1500SS is a compact, top-quality 2-track monophonic solid-state tape recorder. Powerful, solid-state amplifier, and high efficiency speaker provide big, rich tone. Lightweight, and with push button operating ease, the 1500SS is built for a wide range of uses.

ADVANCED FEATURES OF THE 1500SS MONOPHONIC TAPE RECORDER: 2 track mono record/playback + solid-state push-pull output amplifier + simple keyboard operation + dual speed + all-metal construction + V.U. meter record indicator + self-adjusting braking system + digital tape counter + instant pause control + fast forward and rewind with interlocking safety controls + provision for monitoring and P.A. use + automatic head demagnetization + automatic tape lifters + accepts accessory foot control with no modification + complete with dynamic microphone, 1 pin-pin and 1 pin-phone patch cord, blank tape and self-threading take-up reel.



All inputs and outputs for recording or playing back through any source are conveniently grouped on one rear panel.

SPECIFICATIONS 1500SS Monophonic Recorder

FREQUENCY RESPONSE: 40-15,000 cps $\pm$ 3 db @ 7½ ips
40- 8,000 cps $\pm$ 3 db @ 3¾ ips
(NAB Standard Equalization)

WOW AND FLUTTER: Less than 0.25%

SIGNAL TO NOISE RATIO: Greater than 48 db

POWER OUTPUT: 12 watts peak, 9 watts continuous at less than 5% harmonic distortion

TRACK WIDTH: ½ track, .090" wide

INPUTS: Microphone (Standard Phone Jack); Preamp (Phono Jack)

OUTPUTS: Extension Speaker (Standard Phone Jack)
Preamp (Phono Jack)

SIZE: 6½" x 10¼" x 11¾"

WEIGHT: 18½ lbs.

POWER CONSUMPTION: 105-120 volt, 60 cycle AC only

Revere-Mincom Division **3M**
COMPANY
2501 HUDSON ROAD • ST. PAUL, MINNESOTA 55119

WOLLENSAK 4100 CORDLESS




WOLLENSAK 4100 SPECIFICATIONS:

FREQUENCY RESPONSE:
120-6000 cps $\pm$ 3 db
WOW AND FLUTTER RMS: 0.35%
SIGNAL TO NOISE RATIO:
Better than -45 db
POWER OUTPUT: 250 mW
TRACK WIDTH: 0.06"
PLAYING TIME PER CARTRIDGE:
One hour
TAPE SPEED: 1 7/8 ips.
SIZE: 4 1/2" Width; 7 3/4" Height;
2 1/4" Depth
WEIGHT: 3 Pounds


BATTERY-OPERATED CARTRIDGE TAPE RECORDER OFFERS COMPLETE PORTABILITY. Record a business meeting, classroom lecture or an interview. Easy to load with compact tape cartridges. Easy to use—one 4-position function switch controls all operating modes.

FEATURES OF THE WOLLENSAK 4100: ☐ Records one hour. ☐ Solid-state for instant warmup and reliability. ☐ Constant speed capstan drive. ☐ VU meter for correct recording level and battery condition. ☐ Separate record level and volume controls. ☐ Dynamic microphone with remote start/stop switch. ☐ Record lock safety. ☐ Sturdy construction. ☐ Fully transistorized amplifier. ☐ High efficiency speaker. ☐ Patch cord for external recording/playback. ☐ Complete with sensitive dynamic microphone, carrying case, three SCOTCH® Brand Magnetic Tape Cartridges and standard "C" batteries.

NEW WOLLENSAK 4100 OFFERS THESE UNIQUE FEATURES:




Separate record level and playback volume controls for operating convenience.




Patch cord to record and playback through any sound system.




One 4-position switch controls all operating modes: fast forward, rewind, play/record or off.



Solid-state amplifier for rugged reliability, assures good volume and frequency response.



Capstan drive for constant tape speed. 2 track operation offers one full hour of recording.



VU meter indicates correct recording level and condition of batteries.

Revere-Mincom Division **3M**
COMPANY
2501 HUDSON ROAD • ST. PAUL, MINNESOTA 55119